

AMBIUM®

SLIMBRIGHT-DYNWHT PREMIUM

Constantly improving light output and the quality of light, the Slimbright 300 series is extremely robust and flexible. Guaranteed uniform color bin and lighting. This Slimbright is adjustable in length and very easy to install with tape or mounting clips to suit all your lighting designs and applications.



AMBIUM® SLIMBRIGHT-DYNWHT PREMIUM




SPECIFICATIONS



ARTICLE NUMBER	PRODUCT	COLOR TEMP	LUMEN OUTPUT	POWER	EFFICIENCY	CRI	VOLTAGE	# LEDS	IP RATING	TEMP
		K	LM*	W	LM/W		V			°C
KSB3PW090012	Slimbright 300-DynWHT 1000mm	27-65K	868	9.6	90	85+	24	112	67	-20 to 60
KSB3PW090052	Slimbright 300-DynWHT 5000mm	27-65K	868	9.6	90	85+	24	112	67	-20 to 60

* Lumen values are typical. Allow +/- 10% for color binning tolerance.

Efficiency, lumen output and power output measured with all T, G and B channels 100% power. individual R, G and B channel performance may vary.



DIMENSIONS (MM)

PRODUCT	A1	A2	B1	C1
	mm	mm	mm	mm
Slimbright 300-DYNWHT	1020	125	12.9	5.4

LIGHT DIAGRAM

